## NSN 5985-00-239-6126



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-239-6126 **Application Design:** Audio **Body Style:** Cylindrical w/adjustment knob **Overall Length:** 2.500 inches **Scale Linearity:** Linear **Scale Division Quantity:** 11 **Overall Diameter:** 3.000 inches **Schematic Diagram Designator:** Unbalanced "pi" **Voltage Standing Wave Ratio:** 1.30 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 2.0 watts average **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.2 **Overall Attenuation Range In Decibels:** +0.0/+1.0 **Attenuation Variation Method:** Stepped **Step Position Quantity: Attenuation Per Step In Decibels:** 0.1 **Mounting Facility Type And Quantity:** 2 connector Frequency Range: Between 0.000 megahertz and 900.000 megahertz **Overall Attenuation Accuracy In Decibels: Adjustment Device Type And Quantity:** 

-0.01/+0.01 1 knob Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, male

## NSN 5985-00-239-6126

Variable Attenuator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0