NSN 5985-00-239-7581

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-239-7581

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

4.078 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches

Overall Height:

0.281 inches

Overall Width:

2.255 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average

Mounting Facility Screw Thread Series Designator:

Unf

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.7

Overall Attenuation Range In Decibels:

+0.0/+30.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 5.200 gigahertz and 10.600 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.138 inches

NSN 5985-00-239-7581

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0