NSN 5985-00-240-7420

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-240-7420

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Direction:

Right-hand second flange single connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.622 inches second flange

Flange Inside Height:

0.394 inches first flange

Flange Outside Width:

1.313 inches first flange

Flange Outside Height:

1.312 inches second flange

Flange Inside Diameter:

0.622 inches second flange

Flange Depth:

0.375 inches second flange

Flange Connecting Hole Diameter:

0.144 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.15

Maximum Operating Pressure:

60.0 pounds per square inch gage

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches second flange single connection facility

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

Waveguide Outside Height:

0.391 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

NSN 5985-00-240-7420 Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type first flange
Waveguide Length:
1.000 feet
Flexibility:
Flexible single tubing segment
Material:
Rubber synthetic single tubing jacket
Style Designator:
Straight type
Thread Series Designator:
Unc second flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0