

View Online at <https://aerobasegroup.com/nsn/5985-00-241-5096>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Tubing Twist Type:**

Twistable single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.003 inches all flanges and 1.006 inches all flanges

**Flange Inside Height:**

0.503 inches all flanges and 0.506 inches all flanges

**Flange Outside Width:**

1.610 inches all flanges and 1.640 inches all flanges

**Flange Outside Height:**

1.610 inches all flanges and 1.640 inches all flanges

**Flange Depth:**

0.423 inches all flanges and 0.453 inches all flanges

**Flange Connecting Hole Diameter:**

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.13

**Maximum Operating Pressure:**

15.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Waveguide Longer Offset Distance:**

2.500 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges all connection facilities

**Flange Style:**

Cover type all flanges

**Waveguide Offset Distance:**

2.500 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper alloy all tubing segment and flange

**Precious Material And Location:**

External surfaces rhodium

**Precious Material:**

Rhodium

**Surface Treatment:**

Rhodium single tubing segment outside surfaces

**Style Designator:**

Bend type

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0