NSN 5985-00-242-5034

Variable Attenuator - Page 1 of 2

Application Design:

Audio



View Online at https://aerobasegroup.com/nsn/5985-00-242-5034

Body Style:
Cylindrical w/side terminals
Overall Length:
2.968 inches
Overall Width:
3.125 inches
Body Diameter:
2.750 inches
Scale Linearity:
Nonlinear
Shaft Diameter:
0.250 inches
Shaft Length:
0.656 inches
Body Length:
2.125 inches
Unthreaded Mounting Hole Diameter:
0.093 inches
Schematic Diagram Designator:
C
Distance Between Mounting Facility Centers:
1.500 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Power Rating:
2.0 watts peak
2.0 watts peak Overall Attenuation Range In Decibels:
•
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+30.0
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity:
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 30
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 30 Attenuation Per Step In Decibels:
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 30 Attenuation Per Step In Decibels: 1.0
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 30 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 30 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 2 unthreaded hole
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 30 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 2 unthreaded hole Overall Attenuation Accuracy In Decibels:

NSN 5985-00-242-5034

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A223a0