

View Online at <https://aerobasegroup.com/nsn/5985-00-244-9215>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.020 inches second flange

Flange Inside Height:

0.510 inches second flange

Flange Outside Width:

1.688 inches second flange

Flange Outside Height:

1.688 inches second flange

Flange Depth:

0.500 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.06

Thready Qty Per Inch (tpi):

32 first flange single connection facility

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

1.148 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.020 inches

Waveguide Inside Height:

0.510 inches

Waveguide Outside Height:

0.638 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

1.167 feet

Flexibility:

Flexible single tubing segment

Material:

Rubber all tubing jacket

Style Designator:

Straight type

Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0