NSN 5985-00-245-6548

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-245-6548

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.750 inches
Overall Height:
3.281 inches
Overall Width:
3.438 inches
Voltage Standing Wave Ratio:
1.40
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+10.0
+0.0/+10.0 Attenuation Variation Method:
Attenuation Variation Method:
Attenuation Variation Method: Stepped
Attenuation Variation Method: Stepped Step Position Quantity:
Attenuation Variation Method: Stepped Step Position Quantity: 10
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels:
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity:
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 12.400 gigahertz
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity:
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 knob

0.138 inches

NSN 5985-00-245-6548

Variable Attenuator - Page 2 of 2



	Impedance	Rating	ln	Ohms:
--	-----------	--------	----	-------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0