## NSN 5985-00-247-3668

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-247-3668

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b second flange all connection facilities

**Thread Direction:** 

Right-hand second flange all connection facilities

Bend Angle In Deg:

90.0 single bend e-plane

**End Application:** 

Landing control central an/spn-42

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.684 inches first flange and 0.686 inches first flange

Flange Inside Height:

0.222 inches first flange and 0.224 inches first flange

Flange Outside Width:

1.500 inches first flange

Flange Outside Height:

1.000 inches first flange

Flange Inside Diameter:

0.500 inches third flange

Flange Depth:

0.210 inches third flange

Flange Connecting Hole Diameter:

0.144 inches first flange all connection facilities

**Voltage Standing Wave Ratio:** 

1.08

Insertion Loss In Decibels:

0.20

**Waveguide Outside Width:** 

Between 0.358 inches and 0.362 inches

**Thread Size:** 

0.112 inches second flange all connection facilities

Waveguide Inside Width:

Between 0.279 inches and 0.282 inches

**Waveguide Inside Height:** 

Between 0.139 inches and 0.142 inches

**Waveguide Outside Height:** 

Between 0.218 inches and 0.222 inches

## **NSN 5985-00-247-3668** Waveguide Assembly - Page 2 of 2



Waveguide Longer Offset Distance:
1.000 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole first flange all connection facilities
Flange Style:
Contact type first flange
Waveguide Length:
1.280 inches
Waveguide Offset Distance:
0.860 inches
Waveguide Center To Center Distance:
0.320 inches
Waveguide Height:
1.500 inches
Special Features:
One flange accommodates two waveguides
Flexibility:
Rigid single tubing segment
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver single flange inside surfaces
Thread Series Designator:
Unc second flange all connection facilities
Fsc Application Data:
Antennas, waveguides and related equip.
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A073a0