NSN 5985-00-250-3480



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-250-3480 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 14.312 inches **Overall Diameter:** 2.000 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 Input Impedance Rating In Ohms: 46.5 **Output Impedance Rating In Ohms:** 46.5 **Coaxial Connector Series Designation:** Ν **Power Rating:** 5.0 watts average and 10.0 kilowatts peak Rf Signal Attenuation In Decibels: 6.0 **Attenuation Accuracy In Decibels:** -0.10/+0.10 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 1.000 gigahertz and 4.000 gigahertz **Test Data Document:** 81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5985-00-250-3480

Fixed Attenuator - Page 2 of 2



Fiig:

A20000