NSN 5985-00-250-4033

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-250-4033

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
2.812 inches
Overall Width:
2.375 inches
Body Diameter:
2.125 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.312 inches
Shaft Length:
0.500 inches
Body Length:
2.000 inches
Schematic Diagram Designator:
Bridged "t"
Power Rating:
600.0 milliwatts peak
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+40.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
4.0
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 0.000 kilohertz and 30.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-00-250-4033

Variable Attenuator - Page 2 of 2



Yes - demil/mli

Fiig: A223a0