NSN 5985-00-252-1935

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-252-1935

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.340 inches second flange

Flange Inside Height:

2.840 inches second flange

Flange Outside Width:

3.300 inches second flange

Flange Outside Height:

4.500 inches first flange

Flange Depth:

0.500 inches first flange

Flange Connecting Hole Diameter:

0.273 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.02

Maximum Operating Pressure:

35.0 pounds per square inch gage

Waveguide Outside Width:

3.000 inches

Waveguide Inside Width:

2.840 inches

Waveguide Inside Height:

1.340 inches

Waveguide Outside Height:

1.500 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

Flange Style:

Contact type second flange

Waveguide Length:

10.750 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all tubing segment and flange

NSN 5985-00-252-1935

Waveguide Assembly - Page 2 of 2



C		T	4	4 -
Sun	ace	Trea	une	HIT.

Enamel all tubing segment outside surfaces

Style Designator:

Straight type

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A073a0