

View Online at <https://aerobasegroup.com/nsn/5985-00-252-2598>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

Between 2.470 inches and 2.530 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.660 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.840 inches

Overall Height:

1.720 inches

Overall Width:

0.500 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.720 inches

Unthreaded Mounting Hole Diameter:

0.090 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Osm

Power Rating:

2.0 watts peak

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

Overall Attenuation Range In Decibels:

+0.0/+20.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 2.000 gigahertz and 8.000 gigahertz

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Four position rectangular

Shaft Type:

Round, slotted

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0