NSN 5985-00-252-7663

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-252-7663

Body Length:
3.000 inches
Overall Diameter:
2.781 inches
Schematic Diagram Designator:
Bridged "t"
Distance Between Mounting Facility Centers:
1.500 inches
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
20
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 20.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
500.0 input-output
Special Features:
Calibrated dial plate
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

NSN 5985-00-252-7663

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0