

View Online at <https://aerobasegroup.com/nsn/5985-00-253-3488>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Corrugated single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.062 inches second flange

**Flange Inside Height:**

0.505 inches second flange

**Flange Outside Width:**

1.625 inches second flange

**Flange Outside Height:**

1.625 inches first flange

**Flange Inside Diameter:**

1.220 inches first flange

**Flange Depth:**

0.438 inches first flange

**Flange Connecting Hole Diameter:**

0.169 inches single flange all connection facilities

**Voltage Standing Wave Ratio:**

1.15

**Insertion Loss In Decibels:**

0.10

**Maximum Operating Pressure:**

120.0 pounds per square inch gage

**Waveguide Outside Width:**

1.250 inches

**Waveguide Inside Height:**

0.656 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange single connection facility

**Flange Style:**

Cover type second flange

**Waveguide Leg Length:**

2.780 inches

**Waveguide Center To Center Distance:**

1.314 feet

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper alloy single tubing segment

**Precious Material And Location:**

Tubing internal surface silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver single tubing segment inside surfaces

**Style Designator:**

U-bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0