NSN 5985-00-256-0902

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-256-0902

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Passivated
Overall Length:
1.500 inches
Overall Diameter:
0.500 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.25 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.75/+0.75
Unpackaged Unit Weight:
0.300 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 gigahertz and 18.000 gigahertz
Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-00-256-0902

Fixed Attenuator - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000