NSN 5985-00-256-6396

Variable Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-00-256-6396

| Analisation Design. |
|---|
| Application Design: |
| Audio |
| Bushing Length: |
| 0.375 inches |
| Overall Diameter: |
| 1.531 inches |
| Schematic Diagram Designator: |
| Unbalanced "II" |
| Power Rating: |
| 1.0 watts average |
| Mounting Facility Screw Thread Series Designator: |
| Unef |
| Overall Attenuation Range In Decibels: |
| +0.0/+40.0 |
| Attenuation Variation Method: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 1 threaded bushing |
| Overall Attenuation Accuracy In Decibels: |
| -2.00/+2.00 |
| Mounting Thread Quantity: |
| 32 per inch |
| Mounting Facility Screw Thread Diameter: |
| 0.375 inches |
| Impedance Rating In Ohms: |
| 600.0 input |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A223a0 |
| |
| |
| |
| |
| |