## NSN 5985-00-256-8862

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-256-8862

View Online at https://aerobasegroup.com/nsn/5985-00-256-8862
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.250 inches
Overall Height:
2.609 inches
Overall Width:
1.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Distance Between Mounting Facility Centers:
Between 1.115 inches and 1.135 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Tnc
Power Rating:
100.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 1.000 gigahertz
Overall Attenuation Accuracy In Decibels:

-0.15/+0.15

## NSN 5985-00-256-8862

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round

Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0