NSN 5985-00-257-5008

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-257-5008

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.750 inches
Bolt Circle Diameter:
2.250 inches
Overall Height:
Between 2.344 inches and 2.468 inches
Overall Width:
Between 2.938 inches and 3.062 inches
Scale Linearity:
Nonlinear
Scale Division Quantity:
50
Voltage Standing Wave Ratio:
1.50
Power Rating:
10.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+50.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
3 threaded hole
Frequency Range:
Between 4.000 gigahertz and 7.000 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Three position circular
Mounting Facility Screw Thread Diameter:
0.138 inches
Terminal Type And Quantity:
2 connector, coaxial, female

NSN 5985-00-257-5008

Variable Attenuator - Page 2 of 2



Specification Data	a
--------------------	---

99380-104053 manufacturers source control

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A223a0