NSN 5985-00-257-6773

Variable Attenuator - Page 1 of 2



Application Design:

Audio

Body Style:

Cylindrical w/side terminals

Overall Length:

1.812 inches

Overall Width:

1.781 inches

First Flat Length:

0.375 inches

Flat Height:

0.216 inches

Body Diameter:

1.438 inches

Shaft Diameter:

0.250 inches

Bushing Length:

0.375 inches

Shaft Length:

0.750 inches

Body Length:

1.062 inches

Schematic Diagram Designator:

Bridged "t"

Power Rating:

1.0 watts average

Mounting Facility Screw Thread Series Designator:

Unef

Overall Attenuation Range In Decibels:

+0.0/+22.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

1 threaded bushing

Overall Attenuation Accuracy In Decibels:

-2.20/+2.20

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 shaft

Shaft Type:

Round, flatted



NSN 5985-00-257-6773

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.375 inches

Impedance Rating In Ohms:

500.0 input-output

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0