## NSN 5985-00-257-6781

Variable Attenuator - Page 1 of 2

**Application Design:** Transmission line



View Online at https://aerobasegroup.com/nsn/5985-00-257-6781

Body Style:
Cylindrical w/side terminals
Overall Length:
3.0156 inches
Overall Width:
2.6562 inches
Body Diameter:
2.2812 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.9531 inches
Body Length:
2.0625 inches
Distance Between Mounting Facility Centers:
1.500 inches
Power Rating:
500.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+80.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
8
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 50.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-0.40/+0.40
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:

Two position in-line

## NSN 5985-00-257-6781

Variable Attenuator - Page 2 of 2



Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
500.0 input-output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A223a0