NSN 5985-00-257-6791

Variable Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-00-257-6791

Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
2.234 inches
Overall Width:
1.656 inches
Body Diameter:
1.250 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.375 inches
Shaft Length:
0.984 inches
Body Length:
1.250 inches
Schematic Diagram Designator:
Unbalanced "II"
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Mounting Facility Screw Thread Series Designator: Unef
Unef
Unef Overall Attenuation Range In Decibels:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity: 32 per inch
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Shaft Type:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Shaft Type: Round
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Shaft Type: Round Mounting Facility Screw Thread Diameter:
Unef Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 1 threaded bushing Overall Attenuation Accuracy In Decibels: -2.00/+2.00 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Shaft Type: Round Mounting Facility Screw Thread Diameter: 0.375 inches

NSN 5985-00-257-6791

Variable Attenuator - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0