NSN 5985-00-258-0176

Fixed Attenuator - Page 1 of 2

Application Design:

View Online at https://aerobasegroup.com/nsn/5985-00-258-0176



Transmission line **Body Material:** Steel, corrosion resisting **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 1.235 inches **Overall Diameter:** 0.375 inches **Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Voltage Standing Wave Ratio:** 1.35 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 1.0 watts average **Rf Signal Attenuation In Decibels:** 8.0 Voltage Standing Wave Ratio Frequency Range: +7.0/+16.5 gigahertz **Attenuation Accuracy In Decibels:** -0.40/+0.40 **Connection Type Per Function:** Female output and male input **Unpackaged Unit Weight:** 0.350 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector **Frequency Range:** Between 7.000 gigahertz and 16.500 gigahertz **Fsc Application Data:** Antennas, waveguides, and related equipment

NSN 5985-00-258-0176

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000

