NSN 5985-00-259-0423

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-259-0423

Application Design:

Waveguide

Body Material:

Brass

Overall Length:

6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches

Overall Height:

1.625 inches

Overall Width:

3.375 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Voltage Standing Wave Ratio:

1.20

Power Rating:

500.0 milliwatts average

Overall Attenuation Range In Decibels:

+1.0/+18.5

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 9.030 megahertz and 9.190 megahertz

Overall Attenuation Accuracy In Decibels:

-1.00/+1.00

Mounting Facility Pattern:

Four position rectangular

Terminal Type And Quantity:

2 flange

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5985-00-259-0423

Variable Attenuator - Page 2 of 2

Fiig: A223a0

