NSN 5985-00-259-0423

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-259-0423 **Application Design:** Waveguide **Body Material: Brass Overall Length:** 6.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 2.500 inches **Overall Height:** 1.625 inches **Overall Width:** 3.375 inches **Unthreaded Mounting Hole Diameter:** 0.312 inches **Voltage Standing Wave Ratio:** 1.20 **Power Rating:** 500.0 milliwatts average **Overall Attenuation Range In Decibels:** +1.0/+18.5 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 9.030 megahertz and 9.190 megahertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Mounting Facility Pattern:** Four position rectangular **Terminal Type And Quantity:** 2 flange **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a

Unit Of Measure:
-Demilitarization:

NSN 5985-00-259-0423

Variable Attenuator - Page 2 of 2



Fiig:

A223a0