NSN 5985-00-259-3939

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-259-3939

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Scale Linearity:
Linear
Scale Division Quantity:
5
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.000 inches
Operating Tempurature Range:
-4.0/+125.0 degrees fahrenheit
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+100.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
5
Attenuation Per Step In Decibels:
20.0
Mounting Facility Type And Quantity:
2 bracket and 4 unthreaded hole
Frequency Range:
Between 1.000 megahertz and 20.000 megahertz
Overall Attenuation Accuracy In Decibels:
-2.00/+2.00
Mounting Thread Quantity:

32 per inch

NSN 5985-00-259-3939 Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:	
2 slotted screw	
Mounting Facility Pattern:	
our position rectangular	
Mounting Facility Screw Thread Diameter:	
0.138 inches	
mpedance Rating In Ohms:	
50.0 input-output	
Special Features:	
ncl switch	
Precious Material:	
Silver	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A223a0	