

View Online at <https://aerobasegroup.com/nsn/5985-00-259-3939>

**Application Design:**

Transmission line

**Body Material:**

Aluminum

**Body Style:**

Coaxial type

**Overall Length:**

3.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches

**Overall Height:**

2.500 inches

**Overall Width:**

2.500 inches

**Scale Linearity:**

Linear

**Scale Division Quantity:**

5

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

2.000 inches

**Operating Temperature Range:**

-4.0/+125.0 degrees fahrenheit

**Power Rating:**

1.0 watts average

**Mounting Facility Screw Thread Series Designator:**

Unc

**Overall Attenuation Range In Decibels:**

+0.0/+100.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

5

**Attenuation Per Step In Decibels:**

20.0

**Mounting Facility Type And Quantity:**

2 bracket and 4 unthreaded hole

**Frequency Range:**

Between 1.000 megahertz and 20.000 megahertz

**Overall Attenuation Accuracy In Decibels:**

-2.00/+2.00

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

2 slotted screw

**Mounting Facility Pattern:**

Four position rectangular

**Mounting Facility Screw Thread Diameter:**

0.138 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Special Features:**

Incl switch

**Precious Material:**

Silver

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A223a0