## NSN 5985-00-259-5646

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-259-5646

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.062 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
3.600 inches
Overall Width:
2.281 inches
Voltage Standing Wave Ratio:
1.50 and 1.65
Coaxial Connector Series Designation:
Npm
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Unc Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+69.0
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity:
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels:
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz Mounting Thread Quantity:
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz Mounting Thread Quantity: 32 per inch
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+69.0 Attenuation Variation Method: Stepped Step Position Quantity: 69 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 2 knob

0.138 inches

## NSN 5985-00-259-5646

Variable Attenuator - Page 2 of 2



Impedance Ra	ating In	Ohms:
--------------	----------	-------

50.0 input-output

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0