Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-260-2716

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.000 inches

Overall Height:

2.609 inches

Overall Width:

1.875 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Distance Between Mounting Facility Centers:

1.125 inches

Voltage Standing Wave Ratio:

1.20

Coaxial Connector Series Designation:

Tnc

Power Rating:

100.0 milliwatts average

Mounting Facility Screw Thread Series Designator:

Unc

Overall Attenuation Range In Decibels:

+0.0/+1.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

10

Attenuation Per Step In Decibels:

0.1

Mounting Facility Type And Quantity:

2 threaded hole

Frequency Range:

Between 0.000 hertz and 1.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.05/+0.05

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 shaft

NSN 5985-00-260-2716

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round

Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0