

View Online at <https://aerobasegroup.com/nsn/5985-00-264-6890>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches first flange and 1.126 inches first flange

Flange Inside Height:

0.528 inches second flange and 0.531 inches second flange

Flange Outside Width:

1.860 inches first flange and 1.890 inches first flange

Flange Outside Height:

1.860 inches first flange and 1.890 inches first flange

Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Flange Connecting Hole Diameter:

1.169 inches second flange all connection facilities and 1.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.08

Coaxial Connector Series Designation:

Bnc

Connector End Design:

Female

Adapter Length:

4.375 inches

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Special Features:

Includes 5 tuning screws

Material:

Copper alloy second tubing segment and flange

Surface Treatment:

Any acceptable second tubing segment and flange outside surfaces

Style Designator:

Waveguide to waveguide

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0