# NSN 5985-00-268-1392

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-268-1392

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b first flange all connection facilities

#### **Thread Direction:**

Right-hand first flange all connection facilities

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

# Flange Quantity:

2

#### Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

#### Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

#### Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

# Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

# Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

# Flange Depth:

0.610 inches first flange and 0.640 inches first flange

#### Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

# Thready Qty Per Inch (tpi):

32 first flange all connection facilities

# **Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

#### **Thread Size:**

0.164 inches first flange all connection facilities

# Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

# **Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

# **Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

# **Waveguide Longer Offset Distance:**

Between 3.328 inches and 3.348 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

#### Flange Style:

Cover type second flange

# **NSN 5985-00-268-1392** Waveguide Assembly - Page 2 of 2



Waveguide Offset Distance:	
2.016 inches	
Flexibility:	
Rigid single tubing segment	
Material:	
Copper alloy single tubing segment	
Surface Treatment:	
Chromate zinc all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces	
Style Designator:	
Bend type	
Thread Series Designator:	
Unc first flange all connection facilities	
Fsc Application Data:	
Antennas, waveguides, and related equipment	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
Yes - demil/mli	
Filg:	
A073a0	