# NSN 5985-00-270-3139

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-270-3139

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b second flange all connection facilities

#### **Thread Direction:**

Right-hand second flange all connection facilities

# **Tubing Wall Construction Style:**

Seamless single tubing segment

# Flange Quantity:

2

#### Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

#### Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

#### Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

# Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

# Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

# Flange Depth:

0.610 inches first flange and 0.640 inches first flange

#### Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

# **Voltage Standing Wave Ratio:**

0.50

# Thready Qty Per Inch (tpi):

32 second flange all connection facilities

#### **Maximum Operating Pressure:**

30.0 pounds per square inch gage

# **Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

# Thread Size:

0.164 inches second flange all connection facilities

#### Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

# **Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

# **Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

# **NSN 5985-00-270-3139** Waveguide Assembly - Page 2 of 2



Flange Style:
Choke type first flange
Waveguide Length:
5.000 feet
Flexibility:
Rigid single tubing segment
Material:
Rubber natural single tubing jacket
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver single tubing segment inside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc second flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0