NSN 5985-00-270-3142

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-270-3142

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange

Flange Inside Height:

0.505 inches second flange

Flange Outside Width:

1.625 inches second flange

Flange Outside Height:

1.625 inches first flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.15

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

1.125 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

0.900 inches

Waveguide Inside Height:

0.400 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

1.000 feet

NSN 5985-00-270-3142 Waveguide Assembly - Page 2 of 2



Flexibility:
Flexible single tubing segment
Material:
Rubber single tubing jacket
Precious Material And Location:
Flange and tubing inside surface silver
Precious Material:
Silver
Surface Treatment:
Silver single tubing segment inside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0