

View Online at <https://aerobasegroup.com/nsn/5985-00-270-4509>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

Round, terminal/terminals in opposite surface

**Terminal Material:**

Beryllium copper

**Terminal Surface Treatment:**

Gold plated

**Body Surface Treatment:**

Passivated

**Overall Length:**

Between 1.090 inches and 1.250 inches

**Overall Diameter:**

0.390 inches

**Voltage Standing Wave Ratio:**

1.25

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average

**Rf Signal Attenuation In Decibels:**

1.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Connection Type Per Function:**

Female output and male input

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 4.000 gigahertz

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A20000