## NSN 5985-00-272-7451

Variable Attenuator - Page 1 of 2

**Application Design:** 

Audio



View Online at https://aerobasegroup.com/nsn/5985-00-272-7451

Body Style:
Cylindrical w/rear terminals
Overall Length:
2.688 inches
Body Diameter:
2.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
2.063 inches
Overall Diameter:
2.250 inches
Schematic Diagram Designator:
Balanced ladder
Distance Between Mounting Facility Centers:
1.500 inches
Voltage Standing Wave Ratio:
600.00
Mounting Facility Screw Thread Series Designator:
Mounting Facility Screw Thread Series Designator: Unc
Unc
Unc Overall Attenuation Range In Decibels:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 threaded hole
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 threaded hole Mounting Thread Quantity:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 threaded hole Mounting Thread Quantity: 32 per inch
Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 threaded hole Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 threaded hole Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 threaded hole Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern:
Unc Overall Attenuation Range In Decibels: +0.0/+30.0 Attenuation Variation Method: Stepped Step Position Quantity: 10 Attenuation Per Step In Decibels: 3.0 Mounting Facility Type And Quantity: 2 threaded hole Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Two position in-line

## NSN 5985-00-272-7451

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A223a0