

View Online at <https://aerobasegroup.com/nsn/5985-00-275-2817>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b all flanges second connection facility

**Thread Direction:**

Right-hand all flanges second connection facility

**Tubing Wall Construction Style:**

Convolute single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.705 inches all flanges

**Flange Inside Height:**

0.394 inches all flanges

**Flange Outside Width:**

1.313 inches all flanges

**Flange Outside Height:**

1.313 inches all flanges

**Flange Depth:**

0.313 inches all flanges

**Flange Connecting Hole Diameter:**

0.144 inches all flanges first connection facility

**Voltage Standing Wave Ratio:**

1.08

**Maximum Operating Pressure:**

40.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.699 inches and 0.705 inches

**Thread Size:**

0.138 inches second flange all connection facilities

**Waveguide Inside Width:**

Between 0.620 inches and 0.624 inches

**Waveguide Inside Height:**

Between 0.309 inches and 0.313 inches

**Waveguide Outside Height:**

Between 0.388 inches and 0.394 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges first connection facility

**Flange Style:**

Cover type all flanges

**Waveguide Length:**

3.000 feet

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber single tubing jacket

**Precious Material And Location:**

Tubing surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver single tubing segment all surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc all flanges second connection facility

**Fsc Application Data:**

Test console, search, radar

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0