NSN 5985-00-276-3336

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-276-3336

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Interlocked single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange

Flange Inside Height:

0.628 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches first flange all connection facilities

Thready Qty Per Inch (tpi):

32 second flange all connection facilities

Waveguide Outside Width:

1.122 inches

Thread Size:

0.164 inches second flange all connection facilities

Waveguide Inside Width:

0.497 inches

Waveguide Inside Height:

0.625 inches

Waveguide Outside Height:

1.250 inches

Waveguide Longer Offset Distance:

4.062 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole first flange all connection facilities

Flange Style:

Cover type second flange

NSN 5985-00-276-3336 Waveguide Assembly - Page 2 of 2



Waveguide Offset Distance:
4.062 inches
Flexibility:
Rigid single tubing segment
Material:
Copper alloy single tubing segment
Surface Treatment:
Any acceptable single tubing segment all surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc second flange all connection facilities
Specification Data:
81349-mil-w-3970/13 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0