NSN 5985-00-279-9914

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-279-9914

Application Design:
Transmission line
Body Style:
Cylindrical w/side terminals
Overall Length:
3.594 inches
Overall Width:
2.750 inches
First Flat Length:
Between 0.281 inches and 0.344 inches
Flat Height:
0.225 inches
Body Diameter:
2.375 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 1.125 inches and 1.188 inches
Body Length:
2.125 inches
Unthreaded Mounting Hole Diameter:
0.196 inches
Distance Between Mounting Facility Centers:
1.500 inches
Operating Tempurature Range:
-65.0/+175.0 degrees fahrenheit
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.15
Attenuation Accuracy Reference Frequency:
1.0 kilohertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
30
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:

2 threaded hole

NSN 5985-00-279-9914

Variable Attenuator - Page 2 of 2

