NSN 5985-00-280-0940

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-280-0940

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
7.330 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.070 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.100 inches
Overall Height:
1.776 inches
Overall Width:
1.700 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.70
Coaxial Connector Series Designation:
Sm
Power Rating:
Tower Ruting.
2.0 watts average and 500.0 watts peak
-
2.0 watts average and 500.0 watts peak
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity: 7
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity: 7 Attenuation Per Step In Decibels:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity: 7 Attenuation Per Step In Decibels: 10.0
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity: 7 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity: 7 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 4 threaded stud
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity: 7 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 4 threaded stud Frequency Range:
2.0 watts average and 500.0 watts peak Mounting Facility Screw Thread Series Designator: Unc Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 Overall Attenuation Range In Decibels: +0.0/+70.0 Attenuation Variation Method: Stepped Step Position Quantity: 7 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 4 threaded stud Frequency Range: Between 0.000 gigahertz and 18.000 gigahertz

32 per inch

NSN 5985-00-280-0940

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity: 7 slotted screw Mounting Facility Pattern: Four position rectangular Mounting Facility Screw Thread Diameter: 0.138 inches Impedance Rating In Ohms: 50.0 input-output Terminal Type And Quantity: 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A223a0