NSN 5985-00-283-6856

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-283-6856

Application Design:
Audio
Body Style:
Cylindrical w/rear terminals
Overall Length:
2.500 inches
Overall Width:
1.000 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.375 inches
Shaft Length:
0.875 inches
Body Length:
1.266 inches
Schematic Diagram Designator:
" t "
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
5.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.058
Overall Attenuation Range In Decibels:
+46.0/+55.0
Attenuation Accuracy Reference Frequency:
1.0 kilohertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 51.000 hertz and 55.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-9.20/+9.20
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

2 shaft

NSN 5985-00-283-6856

Variable Attenuator - Page 2 of 2



Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches
Impedance Rating In Ohms:
600.0 input-output
Special Features:
Switch spst
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A223a0