NSN 5985-00-287-5067

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-287-5067

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.609 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
6.156 inches
Overall Height:
1.750 inches
Overall Width:
8.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
3.672 inches
Voltage Standing Wave Ratio:
1.25
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.5
1.5 Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+40.0
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 7.000 gigahertz and 11.000 gigahertz
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 7.000 gigahertz and 11.000 gigahertz Overall Attenuation Accuracy In Decibels:
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 7.000 gigahertz and 11.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.50/+1.50
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 7.000 gigahertz and 11.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.50/+1.50 Mounting Thread Quantity:
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 7.000 gigahertz and 11.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.50/+1.50 Mounting Thread Quantity: 32 per inch
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 7.000 gigahertz and 11.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.50/+1.50 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+40.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 7.000 gigahertz and 11.000 gigahertz Overall Attenuation Accuracy In Decibels: -1.50/+1.50 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 knob

0.138 inches

NSN 5985-00-287-5067

Variable Attenuator - Page 2 of 2



Terminal Type And Quanti	ty	:
--------------------------	----	---

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0