

View Online at <https://aerobasegroup.com/nsn/5985-00-287-6327>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Bend Angle In Deg:**

90.0 single bend e-plane

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.705 inches second flange

**Flange Inside Height:**

0.394 inches second flange

**Flange Outside Width:**

1.313 inches second flange

**Flange Outside Height:**

1.312 inches first flange

**Flange Inside Diameter:**

1.000 inches first flange

**Flange Depth:**

0.375 inches first flange

**Flange Connecting Hole Diameter:**

0.144 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.08

**Maximum Operating Pressure:**

40.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.699 inches and 0.705 inches

**Thread Size:**

0.138 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 0.620 inches and 0.624 inches

**Waveguide Inside Height:**

Between 0.309 inches and 0.313 inches

**Waveguide Outside Height:**

Between 0.388 inches and 0.394 inches

**Waveguide Longer Offset Distance:**

4.620 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Offset Distance:**

2.000 inches

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy single tubing segment

**Surface Treatment:**

Any acceptable single tubing segment inside surfaces

**Style Designator:**

Bend type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Test console search, radar set

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0