

View Online at <https://aerobasegroup.com/nsn/5985-00-295-5542>

Application Design:

Audio

Body Style:

Waveguide type

Overall Length:

2.656 inches

Overall Height:

1.906 inches

Overall Width:

2.156 inches

First Flat Length:

0.438 inches

Flat Height:

0.219 inches

Body Diameter:

1.844 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Schematic Diagram Designator:

Unbalanced "lr"

Distance Between Mounting Facility Centers:

1.375 inches

Operating Temperature Range:

-55.0/+120.0 degrees celsius

Power Rating:

600.0 milliwatts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.7

Overall Attenuation Range In Decibels:

+0.0/+12.0

Attenuation Accuracy Reference Frequency:

5.0 kilohertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

12

Attenuation Per Step In Decibels:

1.0

Mounting Facility Type And Quantity:

2 threaded hole

Frequency Range:

Between 0.000 kilohertz and 29.000 kilohertz

Overall Attenuation Accuracy In Decibels:

-0.30/+0.30

Segment Attenuation Range In Decibels:

+0.00/+12.00

Segment Attenuation Accuracy In Decibels:

-0.25/+0.25

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round, flatted

Mounting Facility Screw Thread Diameter:

0.138 inches

Impedance Rating In Ohms:

100000.0 input-output

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0