NSN 5985-00-295-5542

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-295-5542

Application Design:
Audio Audio
Body Style:
Waveguide type
Overall Length:
2.656 inches
Overall Height:
1.906 inches
Overall Width:
2.156 inches
First Flat Length:
0.438 inches
Flat Height:
0.219 inches
Body Diameter:
1.844 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Schematic Diagram Designator:
Unbalanced "Ir"
Distance Between Mounting Facility Centers:
1.375 inches
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
600.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.7
Overall Attenuation Range In Decibels:
+0.0/+12.0
Attenuation Accuracy Reference Frequency:
5.0 kilohertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
12
Attenuation Per Step In Decibels:

NSN 5985-00-295-5542

Variable Attenuator - Page 2 of 2



Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 29.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-0.30/+0.30
Segment Attenuation Range In Decibels:
+0.00/+12.00
Segment Attenuation Accuracy In Decibels:
-0.25/+0.25
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round, flatted
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
100000.0 input-output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A223a0