NSN 5985-00-295-9779

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-295-9779

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

3.002 inches second flange and 3.005 inches second flange

Flange Inside Height:

1.502 inches second flange and 1.505 inches second flange

Flange Outside Diameter:

5.298 inches first flange and 5.328 inches first flange

Flange Depth:

1.235 inches first flange and 1.265 inches first flange

Flange Connecting Hole Diameter:

0.257 inches second flange all connection facilities and 0.260 inches second flange all connection facilities

Thready Qty Per Inch (tpi):

20 first flange all connection facilities

Waveguide Outside Width:

Between 2.994 inches and 3.006 inches

Thread Size:

0.250 inches first flange all connection facilities

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

Waveguide Inside Height:

Between 1.334 inches and 1.346 inches

Waveguide Outside Height:

Between 1.494 inches and 1.506 inches

Waveguide Longer Offset Distance:

10.500 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Offset Distance:

10.500 inches

NSN 5985-00-295-9779 Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid single tubing segment
Material:
Copper alloy all tubing segment and flange
Surface Treatment:
Any acceptable single tubing segment all surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange all connection facilities
Specification Data:
81349-mil-w-3970/13 government specification
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0