NSN 5985-00-296-1950

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-296-1950

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 all bends e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange

Flange Inside Height:

0.628 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches all flanges

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Thready Qty Per Inch (tpi):

32 first flange single connection facility

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

NSN 5985-00-296-1950 Waveguide Assembly - Page 2 of 2



Waveguide Length:
5.317 feet
Waveguide Center To Center Distance:
2.750 inches
Flexibility:
Rigid single tubing segment
Material:
Copper alloy all tubing segment and flange
Surface Treatment:
Chromate zinc all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unc first flange single connection facility
Fsc Application Data:
Radar equipment, except airborne
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A073a0