## NSN 5985-00-296-7656

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-296-7656

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
2.750 inches
Overall Width:
2.750 inches
Body Diameter:
2.750 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.375 inches
Shaft Length:
0.750 inches
Body Length:
2.625 inches
Schematic Diagram Designator:
Unbalanced ladder
Power Rating:
600.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+80.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
8
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 0.000 kilohertz and 15.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-0.40/+0.40
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

2 shaft

## NSN 5985-00-296-7656

Variable Attenuator - Page 2 of 2



Snart Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A223a0