## NSN 5985-00-297-6293

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-297-6293

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.690 inches
Overall Height:
2.690 inches
Overall Width:
3.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.060 inches
Operating Tempurature Range:
-20.0/+75.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Tnc
Power Rating:
1.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
0.5 Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+20.0
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 10.000 megahertz
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 10.000 megahertz Overall Attenuation Accuracy In Decibels:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 10.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 10.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 10.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 40 per inch

Four position rectangular

## NSN 5985-00-297-6293

Variable Attenuator - Page 2 of 2



## **Mounting Facility Screw Thread Diameter:**

0.112 inches

Impedance Rating In Ohms:

50.0 input-output

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0