# NSN 5985-00-299-1323

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-299-1323

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b second flange all connection facilities

#### **Thread Direction:**

Right-hand second flange all connection facilities

#### **Tubing Wall Construction Style:**

Straight seam single tubing segment

# Flange Quantity:

2

#### Flange Inside Width:

2.002 inches first flange and 2.005 inches first flange

#### Flange Inside Height:

1.002 inches first flange and 1.005 inches first flange

#### Flange Outside Diameter:

3.610 inches second flange and 3.640 inches second flange

#### Flange Depth:

0.922 inches second flange and 0.953 inches second flange

# Flange Connecting Hole Diameter:

0.199 inches first flange all connection facilities

# Thready Qty Per Inch (tpi):

32 second flange all connection facilities

#### **Maximum Operating Pressure:**

15.0 pounds per square inch gage

# **Waveguide Outside Width:**

2.000 inches

# **Thread Size:**

0.190 inches second flange all connection facilities

#### **Waveguide Inside Width:**

1.872 inches

# **Waveguide Inside Height:**

0.872 inches

# **Waveguide Outside Height:**

1.000 inches

# Flange Connecting Facility And Quantity:

8 unthreaded hole first flange all connection facilities

# Flange Style:

Cover type first flange

# Waveguide Length:

79.460 inches

#### Flexibility:

Rigid single tubing segment

# NSN 5985-00-299-1323

Waveguide Assembly - Page 2 of 2



Material:
Copper alloy all flange
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unf second flange all connection facilities
Shelf Life:
N/a

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

Fiig:

A073a0