NSN 5985-00-299-1323

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-299-1323

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Straight seam single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches first flange and 2.005 inches first flange

Flange Inside Height:

1.002 inches first flange and 1.005 inches first flange

Flange Outside Diameter:

3.610 inches second flange and 3.640 inches second flange

Flange Depth:

0.922 inches second flange and 0.953 inches second flange

Flange Connecting Hole Diameter:

0.199 inches first flange all connection facilities

Thready Qty Per Inch (tpi):

32 second flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches second flange all connection facilities

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole first flange all connection facilities

Flange Style:

Cover type first flange

Waveguide Length:

79.460 inches

Flexibility:

Rigid single tubing segment

NSN 5985-00-299-1323

Waveguide Assembly - Page 2 of 2



Material:
Copper alloy all flange
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unf second flange all connection facilities
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

Fiig:

A073a0