NSN 5985-00-299-1324

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-299-1324

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Straight seam all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.868 inches all flanges and 1.876 inches all flanges

Flange Inside Height:

0.868 inches all flanges and 0.876 inches all flanges

Flange Outside Diameter:

3.610 inches all flanges and 3.640 inches all flanges

Flange Depth:

0.922 inches all flanges and 0.953 inches all flanges

Thready Qty Per Inch (tpi):

32 all flanges all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches all flanges all connection facilities

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Waveguide Longer Offset Distance:

78.630 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Offset Distance:

1.700 inches

NSN 5985-00-299-1324

Waveguide Assembly - Page 2 of 2



Flexibility:

Rigid single tubing segment

Material:

Copper alloy all flange

Surface Treatment:

Paint all tubing segment and flange outside surfaces

Style Designator:

Corner type

Thread Series Designator:

Unf all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0